



Giesecke+Devrient  
Creating Confidence

# ProNote® 130

Performance you can count on



ProNote 130 has specifically been designed to meet the needs of small retailers and bank branches at a very competitive level. Equipped with a superior LCD display and a sophisticated menu, this banknote counter meets all customer requirements in an easy-to-use, compact, and secure device. ProNote 130 enables the customer to count banknotes with a maximum speed of 1,500 banknotes per minute. Additionally, it provides value counting functionality for easy account balancing.

# Quick and accurate counting



## Precision guaranteed

ProNote 130's precise counting function identifies chained and double banknotes, ensuring that you always get an accurate count. The in-built sensors also enable ProNote 130 to validate the UV and magnetic properties of the processed banknotes.

## Fast and flexible

An ability to define three currencies – in addition to the 16 pre-programmed currencies – provides you with the flexibility to count a broader range of banknotes at speeds of up to 1,500 per minute.

## Value-add

ProNote 130 offers additional benefits, which go well beyond standard piece counting. The value counting mode enables basic accounting and determines the value of pre-sorted banknotes automatically.

## User-friendly design

A smart design and compact dimensions make the device easy to clean and maintain, while a carrying handle provides added portability for use in different locations. A simple-to-use LCD interface and support for software updates make the system easy to adapt to your requirements.

# 1,500

banknotes per minute

Banknotes can be reliably counted at a superior speed, with consistently reliable and accurate results

## TECH FACTS

### Speed:

Counting speed  
up to 1,500 BN/min

Authentication speed  
up to 1,200 BN/min

### Currencies:

up to 16 currencies +  
3 self-defined currencies

### Hopper capacity:

up to 300 BN

### Stacker capacity:

up to 200 BN

### Dimensions (H x W x D):

263 x 268 x 255 mm

### Weight:

6.3 kg

### Temperature range:

0°C–40°C

### Electrical specifications:

AC100–240V, 50/60Hz

### External connections:

RS-232, USB, SD card

